

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS

A fir, 6 ins. diam., bears S.15°W., 50 lks. dist.,
marked T 19 S R 9 W S 29 B T.

A fir, 10 ins. diam., bears N.10°W., 18 lks. dist.,
marked T 19 S R 9 W S 20 B T.

Old cor. bears S.75°E., 10 lks. dist.; I destroy it.

Aug. 18, 1899.

N.89°56'W., on a random line, bet. secs. 20 and 29.

40.00 Set a temp. $\frac{1}{4}$ sec. cor.

80.14 Intersect N. & S. line, 7 lks. N. of the cor. of secs. 19,
20, 29 & 30.

Thence I run

S.89°59'E., on a true line, bet. secs. 20 and 29.

Ascend through burnt timber and dense undergrowth.

11.25 Top of spur, 150 ft. above sec. cor., bears SW.; descend
100 ft. to

21.10 Creek, 2 lks. wide, course SE.; ascend.

40.07 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 20 on N. and 29 on
S. faces; from which

A fir, 4 ins. diam., bears N.17°E., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 5 ins. diam., bears S.6°W., 16 lks. dist.,
marked $\frac{1}{4}$ S B T.

Old cor. bears S., 11 lks. dist.; I destroy it.

47.00 Top of spur, 200 ft. above creek, bears S.; descend 150
ft. to

71.12 Creek, 5 lks. wide, course SW.; ascend.

80.14 The cor. of secs. 20, 21, 28, and 29.

N.0°02'E., bet. secs. 20 and 21.

Descend through timber, partly burnt, and dense under-
growth.

8.20 Creek, 4 lks. wide, 100 ft. below sec. cor., course SW.;
ascend 200 ft. to