

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS	
25.60	Ravine, course SE.; ascend 100 ft. to
36.25	Top of spur, bears SE.; descend.
39.99	Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 17 on N. and 20 on S. faces; from which
	A fir, 12 ins. diam., bears N.10°E., 20 lks. dist., marked $\frac{1}{4}$ S B T.
	A fir, 10 ins. diam., bears S.40°W., 15 lks. dist., marked $\frac{1}{4}$ S B T.
	Old cor. bears S.88°E., 12 lks. dist.; I destroy it.
51.10	Ravine, 200 ft. below spur, course SE.; ascend.
79.98	The cor. of secs. 16, 17, 20 & 21.
	Aug. 19, 1899.
	N.0°02'E., bet. secs. 16 and 17.
	Ascend through partly burnt timber and dense undergrowth.
40.00	Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 17 on W. and 16 on E. faces; from which
	A fir, 5 ins. diam., bears N.60°E., 29 lks. dist., marked $\frac{1}{4}$ S B T.
	A fir, 5 ins. diam., bears S.52°W., 40 lks. dist., marked $\frac{1}{4}$ S B T.
	Old cor. bears E., 15 lks. dist.; I destroy it.
54.00	Summit of ridge, 400 ft. above sec. cor., bears E. & W.; descend 200 ft. to
80.00	The cor. of secs. 8, 9, 16 & 17, established on former survey, which is a post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, marked T 19 S S 9 on NE., R 9 W S 16 on SE., S 17 on SW. and S 8 on NW. faces, with 4 notches on S. and E. edges; from which
	A fir, 5 ins. diam., bears N.48°E., 100 lks. dist., marked T 19 S R 9 W S 9 B T.
	A fir, 5 ins. diam., bears S.32°E., 70 lks. dist., marked T 19 S R 9 W S 16 B T.