

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS

W. and 9 on E. sides; from which

A fir, 14 ins. diam., bears N.73°E., 32 lks. dist.,
marked $\frac{1}{2}$ S B T.

A fir, 8 ins. diam., bears S.23°W., 24 lks. dist.,
marked $\frac{1}{2}$ S B T.

44.70 Creek, 4 lks. wide, 250 ft. below spur, course NW.; ascend
150 ft. to

56.00 Top of spur, bears NW.; descend.

68.40 Old cor. bears E., 5.00 chs. dist.; I destroy it.

68.45 Creek, 10 lks. wide, 200 ft. below spur, course NW.;
ascend 150 ft. to

80.00 Top of spur, bears NW.

A fir, 7 ins. diam., for cor. of secs. 4, 5, 8 & 9, I
mark T 19 S S 4 on NE., R 9 W S 9 on SE., S 8 on SW. and
S 5 on NW. sides, with 5 notches on S. and 4 notches on
E. sides; from which

A fir, 8 ins. diam., bears N.69°E., 13 lks. dist.,
marked T 19 S R 9 W S 4 B T.

A fir, 8 ins. diam., bears S.63°E., 9 lks. dist.,
marked T 19 S R 9 W S 9 B T.

A fir, 18 ins. diam., bears S.50°W., 26 lks. dist.,
marked T 19 S R 9 W S 8 B T.

A fir, 9 ins. diam., bears N.43°W., 6 lks. dist.,
marked T 19 S R 9 W S 5 B T.

Aug. 20, 1899.

S.89°59'W., on a random line, bet. secs. 5 and 8.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.16 Intersect N. and S. line, 16 lks. N. of the cor. of secs.
5, 6, 7 and 8.

Thence I run

N.89°52'E., on a true line, bet. secs. 5 and 8.

Over bottom land, through timber and dense undergrowth.

1.50 Leave bottom, bears NE. & SW.; ascend 150 ft. to

25.00 Top of spur, bears NW.; descend.