

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS	
40.08	A hemlock, 9 ins. diam., for $\frac{1}{4}$ sec. cor., I mark $\frac{1}{4}$ S 5 on N. and 8 on S. sides; from which A hemlock, 7 ins. diam., bears N.85°W., 12 lks. dist., marked $\frac{1}{4}$ S B T. A hemlock, 7 ins. diam., bears S.45°E., 10 lks. dist., marked $\frac{1}{4}$ S B T.
45.00	Old $\frac{1}{4}$ sec. cor. bears S., 12.00 chs. dist.; I destroy it.
46.00	Enter river bottom, 150 ft. below spur, bears NW. and SE.
50.50	D. H. Steven's cabin bears N., about 3.00 chs. dist.
54.00	N. Fork of Smith River, 40 lks. wide, course NW.
56.00	N. Fork of Smith River, 40 lks. wide, course SW.
56.50	Leave bottom, bears NE. & SW.; ascend 300 ft. to
80.16	The cor. of secs. 4, 5, 8, & 9.
<hr/> N.0°02'E., bet. secs. 33 and 34. Ascend through burnt timber and dense undergrowth.	
4.50	Top of spur, 100 ft. above sec. cor., bears NE.; descend 200 ft. to
17.07	Spring branch, 1 lk. wide, course NE.; ascend 200 ft. to
37.00	Top of spur, bears SE.; descend.
40.00	The $\frac{1}{4}$ sec. cor., established on former survey, which is 3 ft. long, a post, $\frac{1}{3}$ ins. sq., set 24 ins. in the ground, marked $\frac{1}{4}$ S 33 on W. and 34 on E. faces; from which A fir, 8 ins. diam., bears N.12°E., 16 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 9 ins. diam., bears S.7°W., 30 lks. dist., marked $\frac{1}{4}$ S B T.
52.06	Creek, 2 lks. wide, 150 ft. below spur, course NE.; ascend 200 ft. to
80.00	The cor. of secs. 27, 28, 33 & 34, established on former survey, which is a post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked T 19 S S 27 on NE., R 9 W S 34 on SE., S 33 on SW. and S 28 on NW. faces, with 1 notch on S. and 3 notches on E. edges; from which A fir, 5 ins. diam., bears N.74°E., 12 lks. dist.,