

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

- CHAINS
40.00 Set a basalt stone, 16x8x7 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which
- An alder, 4 ins. diam., bears S.80°E., 12 lks. dist., marked $\frac{1}{4}$ S 27 B T.
- An alder, 4 ins. diam., bears S.50°W., 23 lks. dist., marked $\frac{1}{4}$ S 28 B T.
- Old cor. bears S.86°E., 10 lks. dist.; I destroy it.
- 45.00 Top of spur, 200 ft. above creek, bears E.; descend.
- 80.00 Set a sandstone, 12x8x8 ins., 8 ins. in the ground, for cor. of secs. 21, 22, 27, and 28, marked with 2 notches on S. and 3 notches on E. edges; from which
- A fir, 5 ins. diam., bears N.70°E., 50 lks. dist., marked T 19 S R 9 W S 22 B T.
- A fir, 4 ins. diam., bears S.19°W., 44 lks. dist., marked T 19 S R 9 W S 27 B T.
- A fir, 6 ins. diam., bears S.76°W., 60 lks. dist., marked T 19 S R 9 W S 28 B T.
- A fir, 6 ins. diam., bears N.37°W., 75 lks. dist., marked T 19 S R 9 W S 21 B T.
- Old cor. bears S.60°E., 15 lks. dist.; I destroy it.
- Aug. 23, 1899.

- S.89°55'W., on a random line, bet. secs. 21 and 28.
- 40.00 Set a temp. $\frac{1}{4}$ sec. cor.
- 79.96 Intersect N. & S. line, 7 lks. S. of the cor. of secs. 20, 21, 28 & 29.
- Thence I run
- N.89°58'E., on a true line, bet. secs. 21 and 28.
- Ascend through burnt timber and dense undergrowth.
- 37.25 Top of spur, 200 ft. above sec. cor., bears SW.; descend.
- 39.98 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 21 on N. and 28 on S. faces; from which
- A fir, 4 ins. diam., bears N.80°E., 40 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 6 ins. diam., bears S.45°W., 15 lks. dist.,