

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS

marked $\frac{1}{4}$ S B T.

Old cor. bears N., 13 lks. dist.; I destroy it.

62.95 Ravine, 200 ft. below spur, course SE.; ascend.

79.96 The cor. of secs. 21, 22, 27 & 28.

N.0°02'E., bet. secs. 21 and 22.

Ascend through partly burnt timber and dense undergrowth.

6.00 Top of spur, 100 ft. above sec. cor., bears SE.; ascend
150 ft. to

29.90 Spring branch, 1 lk. wide, course SE.; ascend.

40.00 The $\frac{1}{4}$ sec. cor., established on former survey, which is
a post, 3 ft. long, 3 ins. sq., set 24 ins. in the
ground, marked $\frac{1}{4}$ S 21 on W. and 22 on E. faces; from
whichA fir, 10 ins. diam., bears N.17°E., 80 lks. dist.,
marked $\frac{1}{4}$ S B T.A fir, 8 ins. diam., bears S.41°W., 63 lks. dist.,
marked $\frac{1}{4}$ S B T.70.00 Top of spur, 200 ft. above branch, bears SW.; descend 100
ft. to

75.90 Ravine, course SW.; ascend.

80.00 Set a sandstone, 16x6x6 ins., 12 ins. in the ground, for
cor. of secs. 15, 16, 21 & 22, marked with 3 notches
on S. and E. edges; from whichA fir, 6 ins. diam., bears N.18°E., 32 lks. dist.,
marked T 19 S R 9 W S 15 B T.A fir, 8 ins. diam., bears S.8°E., 20 lks. dist.,
marked T 19 S R 9 W S 22 B T.A fir, 6 ins. diam., bears S.41°W., 40 lks. dist.,
marked T 19 S R 9 W S 21 B T.A fir, 12 ins. diam., bears N.70°W., 47 lks. dist.,
marked T 19 S R 9 W S 16 B T.

Old cor. bears N.4°W., 12 lks. dist.; I destroy it.

S.89°58'W., on a random line, bet. secs. 16 and 21.