

## Subdivisions of T. 19 S., R. 9 W.

- 40.00 <sup>CHAINS</sup> Set temp.  $\frac{1}{4}$  sec. cor.
- 80.06 Intersect N. & S. line, 14 lks. S. of the cor. of secs. 16, 17, 20 & 21.
- Thence I run
- S.89°56'E., on a true line, bet. secs. 16 and 21.
- Descend through burnt timber and dense undergrowth.
- 31.20 Ravine, 150 ft. below sec. cor., course SE.; ascend.
- 40.03 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 16 on N. and 21 on S. faces; from which
- A fir, 12 ins. diam., bears N.12°E., 40 lks. dist., marked  $\frac{1}{4}$  S B T.
- A fir, 12 ins. diam., bears S.80°W., 26 lks. dist., marked  $\frac{1}{4}$  S B T.
- Old cor. bears S.25°E., 15 lks. dist.; I destroy it.
- 75.00 Top of spur, 200 ft. above last ravine, bears SW.; descend.
- 80.06 The cor. of secs. 15, 16, 21 & 22.

Aug. 24, 1899.

- N.0°02'E., bet. secs. 15 & 16.
- Ascend through partly burnt timber and dense undergrowth.
- 40.00 The  $\frac{1}{4}$  sec. cor. established on former survey, which is a post, 3 ft. long, 3 ins. sq., set 24 ins. in the ground, marked  $\frac{1}{4}$  S 16 on W. and 15 on E. faces; from which
- A fir, 6 ins. diam., bears N.60°E., 76 lks. dist., marked  $\frac{1}{4}$  S B T.
- A fir, 6 ins. diam., bears N.12°W., 18 lks. dist., marked  $\frac{1}{4}$  S B T.
- 56.00 Summit of ridge, 400 ft. above sec. cor., bears E. & W.; descend 150 ft. to
- 60.25 Ravine, course NE.; ascend.
- 80.00 Set a sandstone, 12x8x8 ins., 8 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, marked with 4 notches on S. and 3 notches on E. edges; from which
- A fir, 5 ins. diam., bears N.8°E., 25 lks. dist.,