

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

marked T. 19 S R 9 W S 10 B T.

A fir, 6 ins. diam., bears S.60°E., 27 lks. dist.,  
marked T 19 S R 9 W S 15 B T.

A fir, 4 ins. diam., bears S.21°W., 30 lks. dist.,  
marked T 19 S R 9 W S 16 B T.

A fir, 4 ins. diam., bears N.40°W., 48 lks. dist.,  
marked T 19 S R 9 W S 9 B T.

Old cor. bears S.20°E., 20 lks. dist.; I destroy it.

N.89°56'W., on a random line, bet. secs. 9 and 16.

40.00 Set a temp.  $\frac{1}{2}$  sec. cor.

80.20 Intersect N. and S. line, 23 lks. N. of cor. of secs. 8,  
9, 16, and 17.

Thence I run

N.89°54'E., on a true line, bet. secs. 9 and 16.

Descend through timber and dense undergrowth.

37.00 Ravine, 150 ft. below sec. cor., course NE.; ascend.

40.10 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 9 on N. and 16 on  
S. faces; from which

A fir, 4 ins. diam., bears N.21°E., 12 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

A fir, 7 ins. diam., bears S.10°W., 50 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

Old cor. bears S.75°E., 16 lks. dist.; I destroy it.

54.00 Top of spur, 200 ft. above last ravine, bears NW.; descend.

80.20 The cor. of secs. 9, 10, 15, and 16.

N.0°02'E., bet. secs. 9 and 10.

Ascend through timber and brush.

13.50 Top of spur, 200 ft. above sec. cor., bears NE.; descend  
.150 ft. to

23.54 Creek, 2 lks. wide, course NE.; ascend 200 ft. to

36.56 Top of a spur, bears NE.; descend.

37.00 Old cor. bears E., 3 lks. dist.; I destroy it.