

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS
40.00

- Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 9 on W. and 10 on E. faces; from which
- A fir, 6 ins. diam., bears N.70°E., 10 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 4 ins. diam., bears S.49°W., 15 lks. dist., marked $\frac{1}{4}$ S B T.
- 45.00 Creek, 1 lk. wide, 100 ft. below spur, course E.; ascend 100 ft. to
- 56.00 Top of spur, bears E.; descend 100 ft. to
- 62.25 Creek, 3 lks. wide, course NE.; ascend.
- 65.00 Old sec. cor.; I destroy it.
- 80.00 A fir, 7 ins. diam., for cor. of secs. 3, 4, 9, & 10, I mark T 19 S S 3 on NE., R 9 W S 10 on SE., S 9 on SW. and S 4 on NW. sides, with 5 notches on S. and 3 notches on E. sides; from which
- A fir, 8 ins. diam., bears N.43°E., 25 lks. dist., marked T 19 S R 9 W S 3 B T.
- A fir, 7 ins. diam., bears S.52°E., 25 lks. dist., marked T 19 S R 9 W S 10 B T.
- A fir, 6 ins. diam., bears S.55°W., 14 lks. dist., marked T 19 S R 9 W S 9 B T.
- A fir, 8 ins. diam., bears N.63°W., 8 lks. dist., marked T 19 S R 9 W S 4 B T.

Aug. 25, 1899.

- S.89°54'W., on a random line, bet. secs. 4 and 9.
- 40.00 Set a temp. $\frac{1}{4}$ sec. cor.
- 79.90 Intersect N. and S. line, 21 lks. N. of the cor. of secs. 4, 5, 8 & 9.
- Thence I run
- N.89°45'E., on a true line, bet. secs. 4 and 9.
- Ascend through timber and dense undergrowth.
- 3.75 Summit of ridge, 75 ft. above sec. cor., bears NE. and SW.; descend 40. ft. to