

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS

- N.0°03'E., bet. secs. 26 and 27.  
Through timber and dense undergrowth.
- 0.30 Beaver Creek, 10 lks. wide, course E.; ascend 300 ft. to  
28.00 Top of spur, bears SW.; descend 150 ft. to  
37.20 Ravine, course SW.; ascend.
- 40.00 The  $\frac{1}{4}$  sec. cor., established on former survey, which is a  
basalt stone, 16x10x6 ins., set 12 ins. in the ground,  
marked  $\frac{1}{4}$  on W. face; from which  
A fir, 7 ins. diam., bears N.39°E., 71 lks. dist.,  
marked  $\frac{1}{4}$  S 26 B T.  
A fir, 8 ins. diam., bears S.70°W., 109 lks. dist.,  
marked  $\frac{1}{4}$  S 27 B T.
- 66.50 Top of spur, 200 ft. above last ravine, bears SW.; descend.
- 80.00 Set a basalt stone, 16x10x6 ins., 12 ins. in the ground,  
for the cor. of secs. 22, 23, 26, and 27, marked with  
2 notches on S. and E. edges; and raised a mound of  
stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor. No trees  
within limits.  
The old cor. bears W., 6 lks. dist.; I destroy it.
- 
- S.89°53'W., on a random line, bet. secs. 22 and 27.
- 40.00 Set a temp.  $\frac{1}{4}$  sec. cor.
- 79.92 Intersect N. and S. line, 12 lks. S. of the cor. of secs.  
21, 22, 27 & 28.  
Thence I run  
N.89°58'E., on a true line, bet. secs. 22 & 27.  
Descend through timber, partly burnt, and dense under-  
growth.
- 15.10 Creek, 1 lk. wide, 150 ft. below sec. cor., course SE.;  
ascend 15 ft. to  
28.00 Top of spur, bears S.; descend.
- 39.96 Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 22 on N. and 27 on  
S. faces; from which  
A fir, 5 ins. diam., bears N.70°E., 16 lks. dist.,  
marked  $\frac{1}{4}$  S B T.