

Subdivisions of T. 19 S., R. 9 W.

CHAINS 13.00	Top of spur, bears SW.; descend.
40.02	The $\frac{1}{4}$ sec. cor. established on former survey, which is a post, 3 ft. long, 3 ins. sq., set 24 ins. in the ground, marked $\frac{1}{4}$ S 15 on N. and 22 on S. faces; from which A fir, 5 ins. diam., bears N.65°W., 35 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 6 ins. diam., bears S.9°E., 19 lks. dist., marked $\frac{1}{4}$ S B T.
43.60	Ravine, 125 ft. below spur, course SW.; ascend 375 ft. to
80.04	The cor. of secs. 14, 15, 22 and 23.
	N.0°03'E., bet. secs. 14 and 15. Descend through burnt timber and dense undergrowth.
27.08	Creek, 2 lks. wide, 150 ft. below sec. cor., course NE.; ascend.
40.00	Set a basalt stone, 12x10x8 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 4 ins. diam., bears N.10°E., 43 lks. dist., marked $\frac{1}{4}$ S 14 B T. A fir, 4 ins. diam., bears S.10°W., 7 lks. dist., marked $\frac{1}{4}$ S 15 B T. The old cor. bears S.16°E., 14 lks. dist.; I destroy it.
62.75	Top of spur, 150 ft. above creek, bears NE.; descend.
80.00	Set a basalt stone, 16x10x10 ins., 12 ins. in the ground, for cor. of secs. 10, 11, 14 & 15, marked with 4 notches on S. and 2 notches on E. edges; from which An alder, 8 ins. diam., bears N.12°E., 16 lks. dist., marked T 19 S R 9 W S 11 B T. An alder, 9 ins. diam., bears S.70°E., 20 lks. dist., marked T 19 S R 9 W S 14 B T. An alder, 6 ins. diam., bears S.38°W., 29 lks. dist., marked T 19 S R 9 W S 15 B T. An alder, 5 ins. diam., bears N.20°W., 23 lks. dist., marked T 19 S R 9 W S 10 B T.

The old cor. bears S.60°E., 12 lks. dist.; I destroy it.

Aug. 29, 1899.