

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

| CHAINS | |
|--------|--|
| | S.89°57'W., on a random line, bet. secs. 10 and 15. |
| 40.00 | Set a temp. $\frac{1}{4}$ sec. cor. |
| 79.96 | Intersect N. and S. line, 7 lks. S. of the cor. of secs. 9, 10, 15, and 16. |
| | Thence I run |
| | East, on a true line, bet. secs. 10 and 15. |
| | Descend through timber and brush. |
| 9.00 | Spring branch, 100 ft. below sec. cor., course NE.; ascend 100 ft. to |
| 15.50 | Top of spur, bears N.; descend. |
| 39.98 | Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 10 on N. and 15 on S. faces; from which |
| | A fir, 6 ins. diam., bears N.76°E., 29 lks. dist., marked $\frac{1}{4}$ S B T. |
| | An alder, 6 ins. diam., bears S.20°E., 9 lks. dist., marked $\frac{1}{4}$ S B T. |
| | The old cor. bears S.80°E., 10 lks. dist.; I destroy it. |
| 42.59 | Ravine, 200 ft. below spur, course N.; ascend 200 ft. to |
| 66.00 | Top of spur, bears NW.; descend. |
| 79.96 | The cor. of secs. 10, 11, 14, & 15. |
| | N.0°03'E., bet. secs. 10 and 11. |
| | Descend through partially burnt timber and dense undergrowth. |
| 17.55 | North fork of Smith River, 20 lks. wide, 200 ft. below sec. cor., course NW.; ascend. |
| 40.00 | Set a sandstone, 12x8x8 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which |
| | A fir, 6 ins. diam., bears N.70°E., 50 lks. dist., marked $\frac{1}{4}$ S 10 B T. |
| | A fir, 6 ins. diam., bears S.10°W., 60 lks. dist., marked $\frac{1}{4}$ S 11 B T. |
| | The old cor. bears E., 15 lks. dist.; I destroy it. |
| 68.00 | Top of spur, 200 ft. above river, bears NW.; descend. |
| 80.00 | Set a sandstone, 16x7x6 ins., 12 ins. in the ground, for |