

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

cor. of secs. 2, 3, 10, and 11, marked with 5 notches on S. and 2 notches on E. edges; from which

A fir, 8 ins. diam., bears N.76°E., 28 lks. dist., marked T 19 S R 9 W S 2 B T.

A fir, 9 ins. diam., bears S.30°E., 25 lks. dist., marked T 19 S R 9 W S 11 B T.

A fir, 12 ins. diam., bears S.70°W., 30 lks. dist., marked T 19 S R 9 W S 10 B T.

A fir, 10 ins. diam., bears N.61°W., 53 lks. dist., marked T 19 S R 9 W S 3 B T.

The old cor. bears S., 20 lks. dist.; I destroy it.

West, on a random line, bet. secs. 3 & 10.

40.00 Set temp.  $\frac{1}{2}$  sec. cor..

80.00 Intersect N, and S. line, 5 lks, N. of the cor. of secs. 3, 4, 9, & 10.

Thence I run

N.89°58'E., on a true line, bet. secs. 3 & 10.

Descend through timber and brush.

0.50 Top of spur, bears S.; descend 150 ft. to

21.00 North Fork of Smith River, 30 lks. wide, course N.; ascend along N. slope.

40.00 A fir, 6 ins. diam., for  $\frac{1}{4}$  sec. cor., I mark  $\frac{1}{4}$  S 3 on N. and 10 on S. sides; from which

A fir, 6 ins. diam., bears N.1°E., 11 lks. dist., marked  $\frac{1}{4}$  S B T.

A fir, 9 ins. diam., bears S.66°E., 18 lks. dist., marked  $\frac{1}{4}$  S B T.

The old cor. bears S., 3.00 chs. dist.; I destroy it.

44.50 Top of spur, 150 ft. above river, bears N.; descend 50 ft. to

50.00 Ravine, course N.; ascend 200 ft. to

69.00 Top of spur, bears NE.; descend 100 ft. to

72.06 Spring branch, 1 lk. wide, course NE.; ascend.

80.00 The cor. of secs. 2, 3, 10 and 11.

Aug. 30, 1899.