

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS 17.25	Top of spur, bears SE.; descend.
39.95	Set a sandstone, 12x10x8 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which An alder, 6 ins. diam., bears N.10°E., 20 lks. dist., marked $\frac{1}{4}$ S 26 B T. An alder, 4 ins. diam., bears S.70°W., 30 lks. dist., marked $\frac{1}{4}$ S 35 B T. The old cor. bears N., 10 lks. dist.; I destroy it.
59.80	Ravine, 150 ft. below spur, course SE.; ascend.
79.90	The cor. of secs. 25, 26, 35, and 36.
	East, on a true line, bet. secs. 25 & 36. Ascend through burnt timber and dense undergrowth.
8.00	Top of spur, 100 ft. above sec. cor., bears SE.; descend 200 ft. to
19.15	Creek, 8 lks. wide, course SE.; ascend.
40.00	The $\frac{1}{4}$ sec. cor., established on former survey, which is a basalt stone, 16x7x7 ins., 12 ins. in the ground, marked $\frac{1}{4}$ on N. face; from which A fir, 7 ins. diam., bears N.80°E., 7 lks. dist., marked $\frac{1}{4}$ S 25 B T. A fir, 5 ins. diam., bears S.6°E., 15 lks. dist., marked $\frac{1}{4}$ S 36 B T.
57.00	Top of spur, 150 ft. above creek, bears SE.; descend.
99.90	Intersect the W. bdy. of T. 19 S., R. 8 W., at the closing cor. of secs. 25 and 36, established on former survey, which is a basalt stone, 12x8x7 ins., 8 ins. in the ground, marked C C on W. face, with 1 notch on S. and 5 notches on N. edges; from which A fir, 12 ins. diam., bears N.73°W., 29 lks. dist., marked T 19 S R 9 W S 25 B T. A fir, 10 ins. diam., bears S.19 $\frac{1}{2}$ °W., 22 lks. dist., marked T 19 S R 9 W S 36 B T. This closing cor. is 2.29 chs. S. of the $\frac{1}{4}$ sec. cor. on W. bdy. of Sec. 30, T. 19 S., R. 8 W., which is a post,