

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

marked and witnessed as described by the surveyor  
general.

Sept. 2, 1899.

N.0°04'E., bet. secs. 25 and 26.

Ascend through burnt timber and dense undergrowth.

- 9.50 Top of spur, 100 ft. above sec. cor., bears SE.; descend  
150 ft. to
- 19.07 Creek, 8 lks. wide, course SE.; ascend 200 ft. to
- 34.00 Top of spur, bears W.; descend.
- 40.00 Set a sandstone, 16x6x6 ins., 12 ins. in the ground, for  
 $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face; from which  
A fir, 6 ins. diam., bears N.16°E., 33 lks. dist.,  
marked  $\frac{1}{4}$  S 25 B T.  
A fir, 5 ins. diam., bears S.11°W., 22 lks. dist.,  
marked  $\frac{1}{4}$  S 26 B T.  
The old cor. bears East, 20 lks. dist.; I destroy it.
- 52.58 Creek, 2 lks. wide, 200 ft. below spur, course SW.; ascend  
200 ft. to
- 80.00 The cor. of secs. 23, 24, 25, and 26, established on  
former survey, which is a basalt stone, 16x8x8 ins.,  
12 ins. in the ground, marked with 2 notches on S. and  
1 notch on E. edges, with a mound of stone, 2 ft. base,  
 $1\frac{1}{2}$  ft. high, W. of cor.

N.89°59'W., on a random line, bet. secs. 23 and 26.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.10 Intersect N. and S. line, 12 lks. S. of the cor. of secs.  
22, 23, 26, and 27.  
Thence I run  
S.89°54'E., on a true line, bet. secs. 23 and 26.  
Ascend through partially burnt timber and dense under-  
growth.
- 11.25 Top of spur, 150 ft. above sec. cor., bears SW.; descend  
200 ft. to