

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS

marked T 19 S R 9 W S 25 B T.

This cor. is 2.23 chs. S. of the  $\frac{1}{4}$  sec. cor. on W. bdy. of Sec. 19, T. 19 S., R. 8 W., which is a post, marked and witnessed as described by the surveyor general.

Sept. 3, 1899.

From the cor. of secs. 23, 24, 25, & 26, thence I run N.0°04'E., bet. secs. 23 and 24.

Ascend through timber, partly burnt, and dense undergrowth, along SE. slope of mountain.

40.00 Set a basalt stone, 16x6x6 ins., 12 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor. No trees within limits.

The old cor. bears East, 11 lks. dist.; I destroy it.

80.00 On E. side of mountain, 650 ft. above last sec. cor. Set a basalt stone, 18x9x6 ins., 14 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, marked with 3 notches on S. and 1 notch on E. edges; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor. No trees within limits.

The old cor. bears W., 7 lks. dist.; I destroy it.

N.89°54'W., on a random line, bet. secs. 14 and 23.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 Intersect N. & S. line, 14 lks. N. of the cor. of secs. 14, 15, 22 & 23.

Thence I run

East, on a true line, bet. secs. 14 and 23.

Ascend W. slope of mountain, through scattering timber and dense undergrowth.

40.01 Set a basalt stone, 16x10x10 ins., 12 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor. No trees within limits.

The old cor. bears S.70°E., 15 lks. dist.; I destroy it.