

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 19 S., R. 9 W.

CHAINS 51.00	Summit of mountain, 550 ft. above sec. cor.; descend 300 ft. to.
80.02	The cor. of secs. 13, 14, 23, and 24.
	East, on a true line, bet. secs. 13 & 24. Descend through dead timber and dense undergrowth.
40.00	Set a basalt stone, 14x9x6 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. The old cor. bears S.79°W., 11 lks. dist.; I destroy it.
47.40	Spring branch, 1 lk. wide, 300 ft. below sec. cor., course SE.; ascend 150 ft. to
91.00	Top of spur, bears SE.; descend.
100.20	Intersect the W. bdy. of Tp. 19 S., R. 8 W., at the closing cor. of secs. 13 and 24, established on former survey, which is a fir post, 3 ft. long, 4 ins. sq., set 24 ins. in the ground, marked C C T 19 S R 9 W on W., S 24 on S. and S 13 on N. faces, with 3 grooves on N. and S. faces; from which A fir, 7 ins. diam., bears N.10°W., 23 lks. dist., marked T 19 S R 9 W S 13 B T. A fir, 7 ins. diam., bears S.70°W., 12 lks. dist., marked T 19 S R 9 W S 24 B T. This cor. is 2.45 chs. S. of the $\frac{1}{4}$ sec. cor., on W. bdy. of Sec. 18, T. 19 S., R. 8 W., which is a fir tree, marked and witnessed as described by the surveyor general.
	Sept. 4, 1899.
	From the cor. of secs. 13, 14, 23, and 24, thence I run N.0°04'E., bet. secs. 13 and 14. Descend through scattering timber and dense undergrowth.
17.00	Ravine, 150 ft. below sec. cor., course E.; ascend 200 ft. to
31.50	Top of spur, bears NE.; descend.