

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS	
80.20	<p>Old cor. bears S.83°W., 17 lks. dist.; I destroy it.</p> <p>300 ft. below $\frac{1}{4}$ sec. cor., the cor. of secs. 11, 12, 13, and 14.</p>
	<p>East, on a true line, bet. secs. 12 and 13.</p>
	<p>Descend through timber and brush.</p>
18.45	<p>Spring branch, 1 lk. wide, 150 ft. below sec. cor.,</p>
	<p>course SE.; ascend.</p>
40.00	<p>Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the</p>
	<p>ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 12 on N. and 13 on</p>
	<p>S. faces; from which</p>
	<p>A fir, 10 ins. diam., bears N.79°W., 27 lks. dist.,</p>
	<p>marked $\frac{1}{4}$ S B T.</p>
	<p>A fir, 7 ins. diam., bears S.15°W., 21 lks. dist.,</p>
	<p>marked $\frac{1}{4}$ S B T.</p>
	<p>Old cor. bears S.10°E., 12 lks. dist.; I destroy it.</p>
78.75	<p>Top of spur, 200 ft. above creek, bears N.; descend 150</p>
	<p>ft. to</p>
86.15	<p>Creek, 4 lks. wide, course NW.; ascend.</p>
100.00	<p>Intersect W. bdy. of T. 19 S., R. 8 W., at a point 2.55</p>
	<p>chs. S. of the $\frac{1}{4}$ sec. cor. on W. bdy. of Sec. 7, which</p>
	<p>is a post, marked and witnessed as described by the</p>
	<p>surveyor general, and at point of intersection</p>
	<p>Set a basalt stone, 14x10x6 ins., 9 ins. in the ground,</p>
	<p>for closing cor. of secs. 12 and 13, marked C C on W.</p>
	<p>face, with 4 grooves on S. and 2 grooves on N. faces;</p>
	<p>from which</p>
	<p>A fir, 10 ins. diam., bears N.40°W., 50 lks. dist.,</p>
	<p>marked T 19 S R 9 W S 12 B T.</p>
	<p>A fir, 9 ins. diam., bears S.24°W., 28 lks. dist.,</p>
	<p>marked T 19 S R 9 W S 13 B T.</p>
	<p>Old cor. bears S., 7 lks. dist.; I destroy it.</p>

Sept. 5, 1899.

From the cor. of secs, 11, 12, 13 & 14, thence I run
N.0°04'E., bet. secs. 11 and 12.

Ascend through burnt timber and brush.