

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 19 S., R. 9 W.

CHAINS	
37.00	Top of spur, 200 ft. above sec. cor., bears NE.; descend.
40.00	Set a basalt stone, 12x8x8 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 6 ins. diam., bears N.50°E., 20 lks. dist., marked $\frac{1}{4}$ S 12 B T. A fir, 6 ins. diam., bears S.32°W., 40 lks. dist., marked $\frac{1}{4}$ S 11 B T. Old cor. bears N.69°E., 16 lks. dist.; I destroy it.
64.00	Ravine, 200 ft. below spur, course W.; ascend.
80.00	Set a basalt stone, 13x6x6 ins., 8 ins. in the ground, for cor. of secs. 1, 2, 11 & 12, marked with 5 notches on S. and 1 notch on E. edges; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. No trees within limits. Old cor. bears S.40°E., 12 lks. dist.; I destroy it.
	S.89°58'W., on a random line, bet. secs. 2 and 11.
40.00	Set a temp. $\frac{1}{4}$ sec. cor.
79.96	Intersect N. & S. line, 19 lks. N. of the cor. of secs. 2, 3, 10 & 11. Thence I run N.89°50'E., on a true line, bet. secs. 2 and 11. Ascend through burnt timber and dense undergrowth.
17.00	Summit of divide bet. Smith River and Knowles Creek, 200 ft. above sec. cor., bears N. & S.; descend. Trail to Eugene, bears N. and S., on top of divide; de- scend 200 ft. to
38.20	Knowles Creek, 3 lks. wide, course NW.; ascend.
39.98	Set a basalt stone, 14x9x6 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raised a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Old cor. bears South, 20 lks. dist.; I destroy it.
79.96	The cor. of secs. 1, 2, 11, and 12. East, on a true line, bet. secs. 1 & 12. Ascend through timber and brush.
27.00	Summit of divide bet. Knowles Creek and Whittaker Creek,