

## County Surveyor's Record, Douglas County, Oregon

Portion of West Bdy. of T. 19 S., R. 8 W.

CHAINS

A fir, 16 ins. diam., bears S.55°E., 22 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

51.25 Whittaker Creek, 20 lks. wide, c NE., about 500 ft. below  
last sec. cor., rocky bottom, very swift current; ascend  
steep point and continue along SE. slope, rocky and steep.

71.50 Ravine, c E., about 150 ft. above creek; ascend very  
steep in deadening.

81.00 Top of ridge, c E. & W., 300 ft. above ravine crossing;  
descend steep.

95.50 350 ft. below ridge, intersect 4th Standard Parallel,  
18.40 chs. West of the Standard  $\frac{1}{4}$  S cor. on N. bdy. of  
Sec. 6, where found the SE. bearing tree, a fir, 75 ins.  
diam., marked S C  $\frac{1}{4}$  S B T on NW. face; said tree has  
lain on the ground for many years, but its location,  
when standing, can still be determined. Post and other  
tree could not be found.

Marked a fir, 7 ins. diam.,  $\frac{1}{4}$  S S C on N. face for said  
corner; from which

Said old fir bearing tree brs. S.83°E., 44 lks. dist.

Marked new bearing trees:

A fir, 10 ins. diam., bears S.65°E., 7 lks. dist.,  
marked  $\frac{1}{4}$  S S C B T.

A fir, 48 ins. diam., brs. S.48°W., 75 lks. dist.,  
marked  $\frac{1}{4}$  S S C B T.

At said intersection with said Standard Parallel, set  
post,  $4\frac{1}{2}$  ft. long, 4 ins. sq., 24 ins. in the ground,  
for closing cor. to Tps. 19 S., Rs. 8 & 9 W., marked  
C C T 19 S on S., R 8 W S 6 on E. and R 9 W S 1 on W.  
faces, with 6 notches on E., S. and W. faces; from which

A fir, 18 ins. diam., bears S.40 $\frac{3}{4}$ °E., 40 lks. dist.,  
marked T 19 S R 8 W S 6 B T.

A fir, 12 ins. diam., bears S.15 $\frac{3}{4}$ °W., 27 lks. dist.,  
marked T 19 S R 9 W S 1 B T.

A fir, 10 ins. diam., bears N.63°W., 27 lks. dist.,  
marked C C T 19 S R 8 & 9 W B T.

Sept. 25th, '91.