

## County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 8 W., W.M.  
Survey by Wm. P. Wright under Contract 486 dated Aug. 1, 1883.

## CHAINS

From the cor. to Townships 20 & 21 S., Rs. 8 & 9 West, which is a post, 6 ins. diam., in ground, marked T 20 S S 31 on NE., R 8 W S 6 on SE., T 21 S S 1 on SW., S 36 on NW. faces, with 6 notches on each edge; from which  
Fir, 12 ins. dia., bears N.61°W., 23 lks. dist.,  
marked T 20 S R 9 W S 36 B T.  
Fir, 12 ins. dia., bears S.68°W., 31 lks. dist.,  
marked T 21 S R 9 W S 1 B T.  
Fir, 6 ins. dia., bears S.31°E., 35 lks. dist.,  
marked T 21 S R 8 W S 6 B T.  
Dogwood, 6 ins. dia., bears N.27°E., 19 lks. dist.,  
marked T 20 S R 8 W S 31 B T.

I run N.89°49'E., on true line, between secs. 31 & 6,  
V.20°E.

58.55 A cedar, 12 ins. dia. for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; from which  
Maple, 12 ins. dia., bears S.20°W., 18 lks. dist.,  
marked  $\frac{1}{4}$  S B T.  
Cedar, 20 ins. dia., bears N.30°W., 4 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

Descend mountain.

60.00 Branch, 2 lks. wide, flows NE.

98.55 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 31 & 32, 5 & 6, marked T 20 S S 32 on NE., R 8 W S 5 on SE., T 21 S S 6 on SW., S 31 on NW. faces, with 1 notch on W. and 5 in E. edges; from which  
Fir, 8 ins. dia., bears N.57°W., 14 lks. dist.,  
marked T 20 S R 8 W S 31 B T.  
Fir, 6 ins. dia., bears N.30°E., 12 lks. dist.,  
marked T 20 S R 8 W S 32 B T.  
Maple, 10 ins. dia., bears S.52°W., 60 lks. dist.,  
marked T 21 S R 8 W S 6 B T.  
Maple, 9 ins. dia., bears S.64°E., 10 lks. dist.,  
marked T 21 S R 8 W S 5 B T.