

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 8 W.

CHAINS

N.89°49'E., between secs. 5 & 32.

V.20°E.

Descend mountain.

10.00 Branch, 10 lks. wide, flows N.; ascend.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from whichFir, 10 ins. dia., bears N.28°E., 5 lks. dist.,
marked $\frac{1}{4}$ S B T.Fir, 10 ins. dia., bears S.22°E., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.

Descend.

47.00 Branch, 4 lks. wide, flows South; ascend.

70.00 Descend.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 4, 5, 32 & 33, marked T 20 S S 33 on NE., R 8 W S 4 on SE., T 21 S S 5 on SW., S 32 on NW. faces, with 2 notches on W. & 4 notches on E. edge; from which

Cedar, 20 ins. dia., bears N.85°E., 43 lks. dist.,
marked T 20 S R 8 W S 33 B T.Cedar, 36 ins. dia., bears S.82°E., 43 lks. dist.,
marked T 21 S R 8 W S 4 B T.Cedar, 20 ins. dia., bears S.75°W., 6 lks. dist.,
marked T 21 S R 8 W S 5 B T.Hemlock, 20 ins. dia., bears N.19°W., 74 lks. dist.,
marked T 20 S R 8 W S 32 B T.

N.89°49'E., on true line, between secs. 4 & 33.

V.20°E.

Descend mountain.

30.00 Smith River, 125 lks. wide, flows N.; ascend.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which