

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 8 W.

CHAINS

Fir, 30 ins. dia., bears N.82°W., 25 lks. dist.,
marked T 20 S R 8 W S 34 B T.

Fir, 40 ins. dia., bears S.41°W., 40 lks. dist.,
marked T 21 S R 8 W S 3 B T.

Fir, 40 ins. dia., bears S.35°E., 27 lks. dist.,
marked T 21 S R 8 W S 2 B T.

Fir, 6 ins. dia., bears N.92°E., 47 lks. dist.,
marked T 20 S R 8 W S 35 B T.

N.89°49'E., on true line, between secs. 2 & 35.

V.20°E.

28.00 Branch, 5 lks. wide, flows South.

40.00 A fir, 6 ins. dia., for gr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which

Fir, 4 ins. dia., bears N.30°W., 23 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 6 ins. dia., bears S.45°W., 15 lks. dist.,
marked $\frac{1}{4}$ S B T.

Ascend mountain.

50.00 Top of descent.

65.00 Branch, 4 lks. wide, flows South; ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 1 & 2, 35 & 36,
marked T 20 S S 36 on NE., R 8 W S 1 on SE., T 21 S S
2 on SW., S 35 on NW. faces, with 5 notches on W. & 1
on E. edges; from which

Laurel, 10 ins. dia., bears N.50°E., 27 lks. dist.,
marked T 20 S R 8 W S 36 B T.

Fir, 30 ins. dia., bears S.50°E., 11 lks. dist.,
marked T 21 S R 8 W S 1 B T.

Fir, 30 ins. dia., bears S.41°W., 61 lks. dist.,
marked T 21 S R 8 W S 2 B T.

Fir, 40 ins. dia., bears N.87°W., 80 lks. dist.,
marked T 20 S R 8 W S 35 B T.