

## County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 8 W.

CHAINS

Fir, 48 ins. dia., bears West, 25 lks. dist., marked

 $\frac{1}{4}$  S B T.

Fir, 36 ins. dia., bears S.60°E., 36 lks. dist.,

marked  $\frac{1}{4}$  S B T.

57.00 Cross branch, 3 lks. wide, flows West.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 25 &amp; 36, marked T 20 S R 7 W S 31 on E., T 20 S R 8 W C C S 36 on SW., S 25 on NW. faces, with 5 notches on N. &amp; 1 notch on S. edges; from which

Fir, 24 ins. dia., bears N.54°E., 58 lks. dist.,

marked T 20 S R 7 W S 31 B T.

Maple, 16 ins. dia., bears N.77°W., 72 lks. dist.,

marked T 20 S R 8 W S 25 B T C C.

Fir, 24 ins. dia., bears S.17°W., 73 lks. dist.,

marked T 20 S R 8 W S 36 B T C C.

North on East boundary of Sec. 25.

V.20°E.

Along flat.

7.00 Cross ridge, course NW. &amp; SE.; descend.

39.50 Cross ridge, course NE.

40.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which

Fir, 20 ins. dia., bears S.87°W., 31 lks. dist.,

marked  $\frac{1}{4}$  S B T.

Fir, 20 ins. dia., bears S.72°E., 21 lks. dist.,

marked  $\frac{1}{4}$  S B T.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 24 &amp; 25, marked T 20 S R 7 W S 30 on E., T 20 S R 8 W S 25 C C on SW., S 24 C C on NW. faces, with 4 notches on N. &amp; 2 on S. edges; from which

Fir, 12 ins. dia., bears S.31°E., 31 lks. dist.,