

## County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 8 W.

CHAINS

- 9.00 Cross spur.
- 18.00 Branch, 2 lks. wide, flows West.
- 19.55 Branch, 3 lks. wide, flows SW.
- 40.00 Set post, 4 ins. dia., 4 ft. long, 12 ins. in ground, with marked stone, for gr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which
- Fir, 48 ins. dia., bears N.12°E., 25 lks. dist., marked  $\frac{1}{4}$  S B T.
- Fir, 45 ins. dia., bears N.67°W., 28 lks. dist., marked  $\frac{1}{4}$  S B T.
- 61.00 Cross spur.
- 75.00 Branch, 2 lks. wide, flows SW.
- 77.00 Creek, 15 lks. wide, flows West,; ascend.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 12 & 13, marked T 20 S R 7 W S 18 on E., T 20 S R 8 W S 13 on SW., S 12 on NW. faces, with 2 notches on N. & 4 on S. edges; from which
- Cedar, 45 ins. dia., bears N.25°W., 12 lks. dist., marked T 20 S R 8 W S 12 B T.
- Fir, 40 ins. dia., bears S.85°E., 25 lks. dist., marked T 20 S R 7 W S 18 B T.
- Maple, 28 ins. dia., bears S.61°W., 17 lks. dist., marked T 20 S R 8 W S 13 B T.
- 
- North on East boundary of Sec. 12.
- V.20°E.
- Ascend.
- 25.00 Top of ridge; descend.
- 39.25 Branch, 2 lks. wide, flows West.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which
- Fir, 12 ins. dia., bears S.65°E., 13 lks. dist., marked  $\frac{1}{4}$  S B T.