

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 20 S., R. 8 W.

CHAINS

A fir, 40 ins. dia., bears S.52°W., 7 lks. dist.,
marked $\frac{1}{4}$ S B T.

46.00 Branch, 4 lks. wide, flows SW.

80.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 12 & 1, marked T 20 S
R 7 W S 7 on E., T 20 S R 8 W S 12 C C on SW., S 1 C C
on NW. faces, with 1 notch on N. and 5 on South edges;
from which

Fir, 48 ins. dia., bears N.47°E., 38 lks. dist.,
marked T 20 S R 7 W S 7 B T.

Cedar, 18 ins. dia., bears S.28°W., 42 lks. dist.,
marked T 20 S R 8 W S 12 B T.

Cedar, 20 ins. dia., bears N.64°W., 16 lks. dist.,
marked T 20 S R 8 W S 1 B T.

North on East boundary of Sec. 1.

V.20°E.

Descend.

3.15 Cross branch, 5 lks. wide, flows West; ascend.

29.50 Top of ridge, course E. & W.; descend.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which

Fir, 8 ins. dia., bears S.68°E., 12 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 10 ins. dia., bears S.63°W., 12 lks. dist.,
marked $\frac{1}{4}$ S B T.

62.00 Branch, 4 lks. wide, flows NW.

75.00 Branch, 10 lks. wide, flows West; ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, 12 ins. in ground,
with marked stone, for closing cor. to Town. 19 & 20
S., R. 8 West, with 6 notches on each edge; from which
Fir, 8 ins. dia., bears N.38°E., 17 lks. dist.,
marked T 20 S R 7 W S 6 B T.

Fir, 8 ins. dia., bears S.32°W., 5 lks. dist.,