

County Surveyor's Record, Douglas County, Oregon

East Bay. of T. 20 S., R. 8 W.

CHAINS

marked T 20 S R 8 W S 1 B T.

Fir, 4 ins. dia., bears N.27°W., 22 lks. dist.,

marked T 19 S R 8 W S 36 B T.

Oct. 8th, 1883.

North Bay. of T. 20 S., R. 8 W.

Survey by Wm. P. Wright under Contract No. 486 dated
August 1st, 1883.From the cor. to Town. 19 & 20 S., Rgs. 8 & 9 West, I run
N.89°47'East, on true line, bet. secs. 6 & 31.

V.20½°E.

Ascend mountain.

58.20 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked ¼ S on N.
face; from whichFir, 12 ins. dia., bears N.15°E., 69 lks. dist.,
marked ¼ S B T.Fir, 10 ins. dia., bears S.37°W., 50 lks. dist.,
marked ¼ S B T.

80.00 Cross ridge, course SW. & NE.; descend.

93.00 Branch, 3 lks. wide, flows SE.

98.20 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 5, 6, 31 & 32, marked
T 19 S S 32 on NE., R 8 W S 5 on SE., T 20 S S 6 on
SW., S 31 on NW. faces, with 5 notches on E. & 1 on W.
edges; from whichFir, 20 ins. dia., bears N.33°E., 38 lks. dist.,
marked T 19 S R 8 W S 32 B T.Fir, 20 ins. dia., bears S.54°E., 20 lks. dist.,
marked T 20 S R 8 W S 5 B T.Fir, 24 ins. dia., bears S.9°W., 26 lks. dist.,
marked T 20 S R 8 W S 6 B T.Fir, 20 ins. dia., bears N.35°W., 45 lks. dist.,
marked T 19 S R 8 W S 31 B T.

N.89°47'East, on true line, between secs. 32 & 5.