

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 20 S., R. 8 W.

CHAINS

face; from which

Fir, 40 ins. dia., bears N.12°W., 35 lks. dist.,
marked $\frac{1}{4}$ S B T.

Maple, 18 ins. dia., bears S.35°E., 51 lks. dist.,
marked $\frac{1}{4}$ S B T.

Descend

45.00 Branch, 3 lks. wide, flows South.

47.00 Branch, 5 lks. wide, flows SW.; ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 33, 34, 3 & 4, marked
T 19 S S 34 on NE., R 8 W S 3 on SE., T 20 S S 4 on
SW., S 33 on NW. faces, with 4 notches on W. & 2 on E.
edges; from which

Fir, 30 ins. dia., bears N.43°E., 12 lks. dist.,
marked T 19 S R 8 W S 34 B T.

Fir, 20 ins. dia., bears S.69°E., 24 lks. dist.,
marked T 20 S R 8 W S 3 B T.

Fir, 20 ins. dia., bears S.86°W., 106 lks. dist.,
marked T 20 S R 8 W S 4 B T.

Fir, 36 ins. dia., bears N.15°W., 20 lks. dist.,
marked T 19 S R 8 W S 33 B T.

N.89°47' East, on true line, between secs. 3 & 34.

V.20 $\frac{1}{8}$ °E.

2.00 Descend.

18.00 Branch or spur of mountain, course N. & S.; still descend.

40.00 Set post, 6 ins. dia., 4 ft. long, with marked stone,
12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which

Fir, 18 ins. diam., bears N.10°E., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 12 ins. dia., bears S.70°W., 25 lks. dist.,
marked $\frac{1}{4}$ S B T.

56.00 Ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone,