

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS

marked T 20 S S 25 on NE., R. 8 W S 36 on SE., S 35 on SW., S 26 on NW. faces, with 1 notch on E. & S. edges; from which

Fir, 16 ins. dia., bears N.16°E., 40 lks. dist.,

marked T 20 S R 8 W S 25 B T.

Fir, 18 ins. dia., bears S.27°E., 19 lks. dist.,

marked T 20 S R 8 W S 36 B T.

Fir, 21 ins. dia., bears S.40°W., 100 lks. dist.,

marked T 20 S R 8 W S 35 B T.

Fir, 27 ins. dia., bears N.79°W., 100 lks. dist.,

marked T 20 S R 8 W S 26 B T.

East, on random line, bet. secs. 25 & 36.

V.20°E.

40.00 Set temp. qr. sec. cor.

79.90 Intersect E. bound., 16 lks. South of cor. to secs. 25 & 36.

S.89°53' West, on true line, between secs. 25 & 36.

On top of ridge.

39.95 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N. face; from which

Alder, 16 ins. dia., bears N.42°W., 37 lks. dist.,

marked  $\frac{1}{4}$  S B T.

Alder, 10 ins. dia., bears S.42°E., 40 lks. dist.,

marked  $\frac{1}{4}$  S B T.

Descend.

70.00 Branch, 12 lks. wide, flows SW.; ascend.

80.00 The cor. to secs. 25, 26, 35 & 36.

April 21st, 1884.

North between secs. 25 & 26.

V.20°E.

Descend mountain.

40.00 Set post, 4 ins. dia., 4 ft. long, in mound of rock, 18