

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS

ins. high, 3 ft. sqr. at base, for qr. sec. cor., marked  $\frac{1}{4}$  S on W. face. No witness trees.

42.00 Branch, 2 lks. wide, flows SE.; ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, in mound of rock, 18 ins. high, 3 ft. sqr. at base, for cor. to secs. 23, 24, 25, & 26, marked T 20 S S 24 on NE., R 8 W S 25 on SE., S 26 on SW., S 23 on NW. face, with 1 notch on E. & 2 on S. edges. No witness trees.

East, on random line, bet. secs. 24 & 25.

V.20°E.

40.00 Set temp. qr. sec. cor.

79.85 Intersect East bound., 22 lks. South of cor. to secs. 24 & 25.

S.89°51'W., on true line, between secs. 24 & 25.

5.00 Branch, 2 lks. wide, flows SW.; ascend mountain.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N. face; from which

Fir, 16 ins. dia., bears N.72°W., 91 lks. dist., marked  $\frac{1}{4}$  S B T.

Fir, 20 ins. dia., bears S.17°E., 10 lks. dist., marked  $\frac{1}{4}$  S B T.

Descend mountain.

48.00 Branch, 2 lks. wide, flows S.80°W.

60.00 Along North side of same branch.

79.85 The cor. to secs. 23, 24, 25 & 26.

North between secs. 23 & 24.

V.20°E.

Descend mountain.

15.00 Branch, 10 lks. wide, flows SW.; ascend.

40.00 Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18 ins. high, 3 $\frac{1}{2}$  ft. sqr. at base, for qr. sec. cor., marked  $\frac{1}{4}$  S on W. face. No witness trees.