

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

SE., S 14 on SW., S 11 on NW. face, with 4 notches on S. & 1 on East edge. No witness trees.

East, on random line, between secs. 12 & 13.

V.20°E.

40.00 Set temp. qr. sec. cor.

79.95 Intersect East boundary of township, 50 lks. South of cor. to secs. 12 & 13.

S.89°39'W., on true line, between secs. 12 & 13.

Along mountain, sloping South.

39.97 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

Fir, 10 ins. dia., bears S.16°W., 63 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 15 ins. dia., bears N.23°E., 72 lks. dist., marked $\frac{1}{4}$ S B T.

79.95 The cor. to secs. 11, 12, 13 & 14.

April 24th.

North between sections 11 & 12.

V.20°E.

Ascend mountain.

10.00 Top of ridge and descend.

35.00 Branch, 5 lks. wide, flows West. Ascend mountain.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which

Fir, 6 ins. dia., bears N.22°W., 47 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 7 ins. dia., bears S.72°E., 50 lks. dist., marked $\frac{1}{4}$ S B T.

Still ascend.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 1, 2, 11 & 12,