

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

marked T 20 S S 1 on NE., R 8 W S 12 on SE., S 11 on SW., S 2 on NW. face, with 5 notches on S. & 1 on E. edge; from which

Fir, 6 ins. dia., bears N.22°E., 20 lks. dist.,
marked T 20 S R 8 W S 1 B T.

Fir, 8 ins. dia., bears S.25°E., 27 lks. dist.,
marked T 20 S R 8 W S 12 B T.

Fir, 9 ins. dia., bears S.40°W., 50 lks. dist.,
marked T 20 S R 8 W S 11 B T.

Fir, 4 ins. dia., bears N.42°W., 55 lks. dist.,
marked T 20 S R 8 W S 2 B T.

East, on random line, between secs. 1 & 12.

V.20°E.

40.00 Set temp. gr. sec. cor.

79.50 Intersect East bound. of township, 50 lks. South of cor.
to secs. 1 & 12.

S.89°39' West, on true line, between secs. 1 & 12.

Along mountain top.

39.75 Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18
ins. high, 3 ft. sqr. at base, for gr. sec. cor.,
marked $\frac{1}{2}$ S on N. face. No witness trees.

79.50 The cor. to secs. 1, 2, 11 & 12.

North, on random line, between secs. 1 & 2.

V.20°E.

40.00 Set temp. gr. sec. cor.

80.10 Intersect North bound. of Town., 16 lks. East of cor. to
secs. 35, 36, 1 & 2.

S.7° East, on true line, between secs. 1 & 2.

Ascend mountain.

5.00 Descend.

20.00 Ascend.

40.10 Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18
ins. high, 3 ft. sqr. at base, for gr. sec. cor.,