

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

- marked $\frac{1}{4}$ S on W. face. No witness trees.
- 80.10 The cor. to secs. 1, 2, 11 & 12.
- April 25th.
-
- From the cor. to secs. 34, 35, 2 & 3, on south bound. of township, I run
- North between secs. 34 & 35.
- V.20°E.
- Along ridge, sloping East.
- 40.00 Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18 ins. high, 3 ft. sqr. at base, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face.
- 80.00 Set post, 6 ins. dia., 4 ft. long, in mound of stone, 18 ins. high, 3 ft. sqr. at base, for cor. to secs. 26, 27, 34 & 35, marked T 20 S S 26 on NE., R 8 W S 35 on SE., S 34 on SW., S 27 on NW. face, with 1 notch on S. & 2 on East edge. No witness trees.
-
- East, on random line, between secs. 26 & 35.
- V.20°E.
- 40.00 Set temp. qr. sec. cor.
- 80.10 Intersect N. & S. line, 10 lks. South of cor. to secs. 25, 26, 35 & 36; thence
- S.89°56' West, on true line, between secs. 26 & 35.
- Descend mountain.
- 20.00 Branch, 10 lks. wide, flows SW.; ascend mountain.
- 40.05 Set post, 4 ins. dia., 4 ft. long, in ground 12 ins. with marked stone, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- Alder, 16 ins. dia., bears S.41°W., 95 lks. dist., marked $\frac{1}{4}$ S B T.
- Alder, 22 ins. dia., bears S.40°E., 105 lks. dist., marked $\frac{1}{4}$ S B T.
- Still ascend.
- 80.10 The cor. to secs. 26, 27, 34 & 35.