

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

- 40.00^{CHAINS} Set post, 4 ins. dia., 4 ft. long, in ground 12 ins. with marked stone, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Alder, 6 ins. dia., bears N.55°E., 42 lks. dist., marked $\frac{1}{4}$ S B T.
- Alder, 8 ins. dia., bears S.42°W., 90 lks. dist., marked $\frac{1}{4}$ S B T.
- 60.00 Descend mountain sloping NE.
- 80.00 Set post, 6 ins. dia., 4 ft. long, in mound of stone, 18 ins. high, 3 ft. sqr. at base, for cor. to secs. 14, 15, 22 & 23, marked T 20 S S 14 on NE., R 8 W S 23 on SE., S 22 on SW., S 15 on NW. face. No witness trees near.
- April 28th, 1884.

- East, on random line, bet. secs. 14 & 23.
- V.20°E.
- 40.00 Set temp. gr. sec. cor.
- 79.81 Intersect N. & S. line, 35 lks. South of cor. to secs. 15, 14, 23 & 24; thence
- S.89°45'West, on true line, bet. secs. 14 & 23.
- Descend spur sloping NW.
- 39.90 Branch, 2 lks. wide, flows N.; ascend.
- 39.91 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- Alder, 4 ins. dia., bears N.22°E., 5 lks. dist., marked $\frac{1}{4}$ S B T.
- Alder, 7 ins. dia., bears S.27°W., 10 lks. dist., marked $\frac{1}{4}$ S B T.
- Ascend mountain.
- 79.81 The cor. to secs. 14, 15, 22 & 23.

North between secs. 14 & 15.

V.20°E.

Descend mountain gradually.