

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS 40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which <p style="margin-left: 40px;">Fir, 6 ins. dia., bears N.78°E., 49 lks. dist.,  marked <math>\frac{1}{4}</math> S B T.</p> <p style="margin-left: 40px;">Fir, 7 ins. dia., bears S.79°E., 50 lks. dist.,  marked <math>\frac{1}{4}</math> S B T.</p>
62.50	Branch, 10 lks. wide, flows West; ascend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 10, 11, 14 & 15, marked T 21 S S 11 on NE., R 8 W S 14 on SE., S 15 on SW., S 10 on NW. faces, with 4 notches on S. & 2 on East edge; from which <p style="margin-left: 40px;">Fir, 8 ins. dia., bears N.20°E., 27 lks. dist.,  marked T 20 S R 8 W S 11 B T.</p> <p style="margin-left: 40px;">Fir, 6 ins. dia., bears S.25°E., 40 lks. dist.,  marked T 20 S R 8 W S 14 B T.</p> <p style="margin-left: 40px;">Fir, 9 ins. dia., bears S.60°W., 50 lks. dist.,  marked T 20 S R 8 W S 15 B T.</p> <p style="margin-left: 40px;">Fir, 10 ins. dia., bears N.72°W., 62 lks. dist.,  marked T 20 S R 8 W S 10 B T.</p>
	East, on random line, between secs. 11 & 14. <p style="margin-left: 100px;">V.20°E.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.72	Intersect N. & S. line, 42 lks. South of cor. to secs. 11, 12, 13 & 14; thence S.89°42'W., on true line, between secs. 11 & 14. <p style="margin-left: 100px;">V.20°E.</p>
	Descend mountain.
23.00	Branch, 5 lks. wide, flows SW.; ascend.
39.86	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which <p style="margin-left: 40px;">Fir, 10 ins. dia., bears N.42°E., 75 lks. dist.,  marked <math>\frac{1}{4}</math> S B T.</p>