

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

Oak, 10 ins. dia., bears N.49°E., 61 lks. dist.,
marked T 20 S R 8 W S 27 B T.

Fir, 12 ins. dia., bears S.44°E., 62 lks. dist.,
marked T 20 S R 8 W S 34 B T.

Alder, 12 ins. dia., bears S.45°W., 23 lks. dist.,
marked T 20 S R 8 W S 33 B T.

Fir, 10 ins. dia., bears N.68°W., 35 lks. dist.,
marked T 20 S R 8 W S 28 B T.

East, on random line, between secs. 27 & 34.

V.20°E.

40.00 Set temp. qr. sec. cor.

80.20 Intersect N. & S. line, 27 lks. South of cor. to secs.
26, 27, 34 & 35; thence

S.89°48' West, on true line, between secs. 27 & 34.

Ascend mountain.

10.00 Branch, 1 lk. wide, flows SE.; still ascend.

40.10 Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18
ins. high, 3½ ft. at base, for qr. sec. cor., marked
¼ S on N. face; from which there are no witness trees.
Still ascend.

50.00 Flat on mountain.

80.20 The cor. to secs. 27, 28, 33 & 34.

May 2nd, 1884.

North between secs. 27 & 28.

V.20½°E.

Descend.

36.50 Branch, 2 lks. wide, flows West.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked ¼ S on W.
face; from which

Hemlock, 8 ins. dia., bears N.72°E., 18 lks. dist.,
marked ¼ S B T.

Hemlock, 10 ins. dia., bears S.87°W., 19 lks. dist.,
marked ¼ S B T.