

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS	
	V.20°E.
40.00	Set temp. qr. sec. cor.
79.90	Intersect N. & S. line, 55 lks. South of cor. to secs. 10, 11, 14 & 15; thence S.89°36'West, on true line, between secs. 10 & 15. Along mountain side, sloping South.
39.95	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground; raised mound of stone alongside. No witness trees. Descend.
79.90	The cor. to secs. 9, 10, 15 & 16.
	North between sections 9 & 10. V.20°E.
	Ascend mountain.
10.00	Top of ridge; descend.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 36 ins. dia., bears N.60°W., 22 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 40 ins. dia., bears N.67°E., 22 lks. dist., marked $\frac{1}{4}$ S B T. Along ridge, sloping West.
57.00	Descend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 4, 3, 9 & 10, marked T 20 S S 3 on NE., R 8 W S 10 on SE., S 9 on SW., S 4 on NW. face, with 5 notches on S. & 3 on E. edge; from which Fir, 40 ins. dia., bears N.63°E., 58 lks. dist., marked T 20 S R 8 W S 3 B T. Fir, 12 ins. dia., bears S.10°E., 39 lks. dist., marked T 20 S R 8 W S 10 B T. Fir, 36 ins. dia., bears S.36°W., 25 lks. dist., marked T 20 S R 8 W S 9 B T.