

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS

Fir, 6 ins. dia., bears N.55°W., 8 lks. dist.,  
marked T 20 S R 8 W S 4 B T.

East, on random line, between secs. 3 & 10.

V.20°E.

40.00 Set temp. gr. sec. cor.

79.70 Intersect N. & S. line, 59 lks. South of cor. to secs. 2,  
3, 10 & 11; thence

S.89°35'West, on true line, between secs. 3 & 10.

On mountain top.

39.85 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for gr. sec. cor., marked  $\frac{1}{2}$  S on N,  
face; raised mound of stone alongside. No witness  
trees.

Descend.

79.70 The cor. to secs. 3, 4, 9 & 10.

May 6th, 1884.

North, on random line, between secs. 3 & 4.

V.20°E.

40.00 Set temp. gr. sec. cor.

79.90 Intersect N. bound. of Town., 19 lks. East of cor. to  
secs. 3, 4, 33 & 34; thence

S.8°East, on true line, between secs. 3 & 4.

Descend mountain, sloping SW.

39.90 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for gr. sec. cor., marked  $\frac{1}{2}$  S on W.  
face; raised mound of stone alongside. No witness trees.

79.90 The cor. to secs. 3, 4, 9 & 10.

From cor. to secs. 32 & 33, 4 & 5, on S. bound. of town-  
ship, I run

North between secs. 32 & 33.

V.20°E.

Along East slope of mountain.