

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS	
20.50	Cross ridge, E. & W.; descend.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Cedar, 36 ins. dia., bears S.30°W., 10 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 10 ins. dia., bears S.12°E., 11 lks. dist., marked $\frac{1}{4}$ S B T.
50.75	Branch, 5 lks. wide, flows East; ascend.
59.00	Top of hill; descend.
66.50	Branch, 6 lks. wide, flows East; ascend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 28, 29, 32 & 33, marked T 20 S S 28 on NE., R 8 W S 33 on SE., S 32 on SW., S 29 on NW. face, with 4 notches on E. and 1 on S. edge; from which Fir, 12 ins. dia., bears N.38°E., 9 lks. dist., marked T 20 S R 8 W S 28 B T. Fir, 7 ins. dia., bears S.47°E., 7 lks. dist., marked T 20 S R 8 W S 33 B T. Fir, 14 ins. dia., bears S.63°W., 29 lks. dist., marked T 20 S R 8 W S 32 B T. Fir, 7 ins. dia., bears N.47°W., 36 lks. dist., marked T 20 S R 8 W S 29 B T.
	East, on random line, between secs. 28 & 33. V.20 $\frac{1}{2}$ °E.
40.00	Set temp. gr. sec. cor.
80.10	Intersect N. & S. line, 35 lks. South of cor. to secs. 27, 28, 33 & 34. S.89°45'West, on true line, between secs. 28 & 33. Along mountain, sloping SW.
10.00	In bottom.
40.05	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on