

## Subdivisions of T. 20 S., R. 8 W.

CHAINS

N. face; from which

Fir, 12 ins. dia., bears N.23°W., 28 lks. dist.,

marked  $\frac{1}{4}$  S B T,

Fir, 30 ins. dia., bears S.10°E., 36 lks. dist.,

marked  $\frac{1}{4}$  S B T.

46.00 Smith River, flows NE., 130 lks. wide; ascend.

80.10 The cor. to secs. 28, 29, 32 &amp; 33.

May 7th, 1884.

North between secs. 28 &amp; 29.

V.20°E.

Along ridge sloping East.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on W, face; from which

Hemlock, 4 ins. dia., bears N.75°W., 17 lks. dist.,

marked  $\frac{1}{4}$  S B T.

Cedar, 6 ins. dia., bears S.18°E., 24 lks. dist.,

marked  $\frac{1}{4}$  S B T.

80.00 Fir, 20 ins. dia. for cor. to secs. 20, 21, 28 &amp; 29, marked T 20 S S 21 on NE., R 8 W S 28 on SE., S 29 on SW., S 20 on NW. face, with 4 notches on E. &amp; 2 on South edges; from which

Fir, 36 ins. dia., bears S.50°W., 32 lks. dist.,

marked T 20 S R 8 W S 29 B T.

Fir, 36 ins. dia., bears N.45°W., 48 lks. dist.,

marked T 20 S R 8 W S 20 B T.

Fir, 36 ins. dia., bears N.60°E., 62 lks. dist.,

marked T 20 S R 8 W S 21 B T.

Hemlock, 6 ins. dia., bears S.30°E., 53 lks. dist.,

marked T 20 S R 8 W S 28 B T.

East, on random line, between secs. 21 &amp; 28.

V.20°E.

40.00 Set temp. qr. sec. cor.