

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS 80.12	Intersect N. & S. line, 40 lks. South of cor. to secs. 21, 22, 27 & 28; thence S.89°43' West, on true line, between secs. 21 & 28.
8.50	Smith River; in and down river.
14.00	Leave river bed, flowing SW.
40.06	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Fir, 30 ins. dia., bears N.45°W., 21 lks. dist., marked $\frac{1}{4}$ S B T. Hemlock, 20 ins. dia., bears S.65°W., 34 lks. dist., marked $\frac{1}{4}$ S B T.
	Along bottom.
50.00	Smith River, 130 lks. wide, flows NW.
62.75	Branch, 6 lks. wide, flows Northwest; ascend.
80.12	The cor. to secs. 20, 21, 28 & 29.
	North between secs. 20 & 21. V.20°E.
	Along west slope of mountain.
26.00	Descend.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 10 ins. dia., bears S.51°W., 30 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 40 ins. dia., bears N.60°W., 9 lks. dist., marked $\frac{1}{4}$ S B T.
53.00	Cross Smith River, 110 lks. wide, flows West; ascend.
66.00	Top of spur; descend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 16, 17, 20 & 21, marked T 20 S S 16 on NE., R 8 W S 21 on SE., S 20 on SW., S 17 on NW. face, with 4 notches on E. & 3 on S. edge; from which