

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

Maple, 24 ins. dia., bears N.56°E., 87 lks. dist.,
marked T 20 S R 8 W S 16 B T.

Maple, 7 ins. dia., bears S.41°E., 26 lks. dist.,
marked T 20 S R 8 W S 21 B T.

Fir, 40 ins. dia., bears S.48°W., 69 lks. dist.,
marked T 20 S R 8 W S 20 B T.

Maple, 24 ins. dia., bears N.61°W., 36 lks. dist.,
marked T 20 S R 8 W S 17 B T.

May 8th, 1884.

East, on random line, between secs. 16 & 21.

V.20½°E.

40.00 Set temp. gr. sec. cor.

79.90 Intersect N. & S. line, 35 lks. South of cor. to secs.
15, 16, 21 & 22; thence

S.89°45'West, on true line, bet. secs. 16 & 21.

Along bottom.

3.00 Creek, 50 lks. wide, flows N.

8.00 Same, flows SW.

13.00 Branch, 8 lks. wide, flows S.

39.95 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked ¼ S on N.
face; from which

Fir, 30 ins. dia., bears N.80°E., 23 lks. dist.,
marked ¼ S B T.

Fir, 36 ins. dia., bears S.70°E., 6 lks. dist.,
marked ¼ S B T.

56.00 Creek, 50 lks. wide, flows NW.

79.90 The cor. to secs. 16, 17, 20 & 21.

North between secs. 16 & 17.

V.20½°E.

In bottom.

11.00 Cross creek, 50 lks. wide, flows W.

19.75 Same creek, 50 lks. wide, flows NE.