

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

| CHAINS | |
|--------|--|
| 21.50 | Same creek, 50 lks. wide, flows West.. |
| 40.00 | Set post, 4 ins. dia., 4 ft. long, 12 ins. in ground with marked stone, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 20 ins. dia., bears N.20°W., 36 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 12 ins. dia., bears S.50°E., 22 lks. dist., marked $\frac{1}{4}$ S B T. |
| 40.25 | Branch, 2 lks. wide, flows NW.; ascend. |
| 58.00 | Descend. |
| 79.00 | Branch, 1 lk. wide, flows W. |
| 80.00 | Set post, 6 ins. dia., 4 ft. long, 12 ins. in ground with marked stone, for cor. to secs. 8, 9, 16 & 17, marked T 20 S S 9 on NE., R 8 W S 16 on SE., S 17 on SW., S 8 on NW. faces, with 4 notches on E. & S. edges; from which Maple, 20 ins. dia., bears N.70°E., 32 lks. dist., marked T 20 S R 8 W S 9 B T. Fir, 50 ins. dia., bears S.47°E., 56 lks. dist., marked T 20 S R 8 W S 16 B T. Maple, 24 ins. dia., bears S.61°W., 49 lks. dist., marked T 20 S R 8 W S 17 B T. Fir, 48 ins. dia., bears N.23°W., 40 lks. dist., marked T 20 S R 8 W S 8 B T. May 9th, 1884. |

East, on random line, between secs. 9 & 16.

V.20 $\frac{1}{2}$ °E.

| | |
|-------|---|
| 40.00 | Set temp. qr. sec. cor.. |
| 79.85 | Intersect N. & S. line, 40 lks. South of cor. to secs. 9, 10, 15 & 16; thence S.89°43'West, on true line, between secs. 9 & 16. Along bench land. |
| 36.00 | Cross creek, 40 lks. wide, flows NW. |
| 39.92 | Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 |