

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

CHAINS	
	<p>marked T 20 S R 8 W S 8 B T.</p> <p>Fir, 20 ins. dia., bears N.70°W., 17 lks. dist.,</p> <p>marked T-20 S R 8 W S 5 B T.</p>
	<p>East, on random line, between secs. 4 &amp; 9.</p> <p>V.20°E.</p>
40.00	Set temp. qr. sec. cor.
79.80	Intersect N. & S. line, 39 lks. South of cor. to secs. 3, 4, 9 & 10; thence
	S.89°43'West, on true line, between secs. 4 & 9.
	Descend.
18.50	Branch, 5 lks. wide, flows NW.
32.00	Branch, 8 lks. wide, flows SW.
39.00	Branch, 2 lks. wide, flows South.
39.90	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
	Alder, 24 ins. dia., bears N.60°W., 30 lks. dist., marked $\frac{1}{4}$ S B T.
	Fir, 24 ins. dia., bears S.75°E., 13 lks. dist., marked $\frac{1}{2}$ S B T.
55.00	Branch, 15 lks. wide, flows S.
65.00	Branch, 2 lks. wide, flows SE.; ascend.
79.80	The cor. to secs. 4, 5, 8 & 9.
	<p>North, on random line, bet. secs. 4 &amp; 5.</p> <p>V.20°E.</p>
40.00	Set temp. qr. sec. cor.
79.91	Intersect North bound. of Town., 42 lks. East of cor. to secs. 32, 33, 4 & 5; thence
	S.18'E., on true line, bet. secs. 4 & 5.
	On mountain.
39.91	Set post, 4 ins. dia., 4 ft. long, in mound of stone, 18 ins. high, 3 $\frac{1}{2}$ ft. sqr. at base.
42.00	Descend.