

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

## CHAINS

- 28, 29, 32 & 33.  
S.89°49'W., on true line, between secs. 29 & 32.  
Along South slope of mountain.
- 15.25 Branch, 2 lks. wide, flows S.
- 25.30 Branch, 2 lks. wide, flows SE.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N. face; from which  
Cedar, 30 ins. dia., bears S.30°W., 11 lks. dist., marked  $\frac{1}{4}$  S B T.  
Fir, 8 ins. dia., bears N.54°W., 15 lks. dist., marked  $\frac{1}{4}$  S B T.
- 46.50 Cross ridge; descend.
- 59.25 Branch, 2 lks. wide, flows N.
- 72.00 Branch, 2 lks. wide, flows N.
- 80.20 The cor. to secs. 29, 30, 31 & 32.
- 
- West, on random line, between secs. 30 & 31.  
V.20°E.
- 40.00 Set temp. qr. sec. cor.
- 98.60 Intersect West bound. of Town., 20 lks. North of cor. to secs. 25, 36, 30 & 31; thence  
North 89°53' East, on true line, between secs. 30 & 31.
- 19.00 Top of hill; descend.
- 32.00 Branch, 5 lks. wide, flows N.; ascend.
- 58.60 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N. face; from which  
Maple, 6 ins. dia., bears S.7°W., 24 lks. dist., marked  $\frac{1}{4}$  S B T.  
Fir, 40 ins. dia., bears N.48°E., 18 lks. dist., marked  $\frac{1}{4}$  S B T.
- 98.60 The cor. to secs. 29, 30, 31 & 32.  
May 13th.