

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS	<p>Hemlock, 8 ins. dia., bears N.46°W., 23 lks. dist., marked $\frac{1}{4}$ S B T.</p>
60.00	Cross branch, flows N., 8 lks. wide; ascend.
80.20	The cor. to secs. 19, 20, 29 & 30.
	<p>West, on random line, bet. secs. 19 & 30. V.20°E.</p>
40.00	Set temp. qr. sec. cor.
98.50	Intersect West boundary of Town., 47 lks. North of cor. to secs. 24, 25, 19 & 30; thence N.89°42'E., on true line, between secs. 19 & 30. On mountain top, flat.
58.50	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N.face; raised mound of stone alongside. No witness trees.
98.50	The cor. to secs. 19, 20, 29 & 30. May 14th, 1884.
	<p>North between secs. 19 & 20. V.20°E.</p>
	Descend.
12.00	Branch, 3 lks. wide, flows East; ascend.
25.00	Descend.
40.00	Set post, 4 ins. dia., 4 ft. long, 12 ins. in ground, with marked stone, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Cedar, 36 ins. dia., bears S.53°E., 34 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 50 ins. dia., bears N.60°W., 47 lks. dist., marked $\frac{1}{4}$ S B T.
56.00	In bottom, Smith River, 150 lks. wide, flows SW.
68.00	Smith River; flows NE.; 200 lks. wide; ascend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 17, 18, 19 & 20, marked T 20 S S 17 on NE., R 8 W S 20 on SE., S 19 on