

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 8 W.

## CHAINS

SW., S 18 on NW. face, with 3 notches on S. & 5 on E. edges; from which

Fir, 40 ins. dia., bears S.79°E., 19 lks. dist.,  
marked T 20 S R 8 W S 20 B T.

Fir, 40 ins. dia., bears N.76°W., 42 lks. dist.,  
marked T 20 S R 8 W S 18 B T.

Fir, 40 ins. dia., bears S.70°W., 56 lks. dist.,  
marked T 20 S R 8 W S 19 B T.

Fir, 20 ins. dia., bears N.63°E., 70 lks. dist.,  
marked T 20 S R 8 W S 17 B T.

East, on random line, between secs. 17 & 20.

V.20°E.

40.00 Set temp. qr. sec. cor.

80.15 Intersect N. & S. line, 31 lks. South of cor. to secs.  
16, 17, 20 & 21; thence

S.89°47' West, on true line, between secs. 17 & 20.

Along bottom.

6.50 Begin to ascend.

15.00 Descend.

38.50 Branch, 2 lks. wide, flows N.

40.07 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N.  
face; from which

Fir, 7 ins. dia., bears S.40°E., 7 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

Fir, 6 ins. dia., bears N.7°W., 5 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

50.00 Smith River, 120 lks. wide, flows NW.

80.15 The cor. to secs. 17, 18, 19 & 20.

West, on random line, between secs. 18 & 19.

V.20°E.

40.00 Set temp. qr. sec. cor.

98.55 Intersect West boundary of Town., 50 lks. North of cor.