

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

- to secs. 13, 24, 18 & 19; thence
N.89°41'East, on true line, between secs. 18 & 19.
- 13.00 Smith River, 150 lks. wide, flows South; cross bottom.
- 25.00 Begin to ascend.
- 53.00 Cross ridge, NW. & SE.; descend.
- 58.55 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which
- Maple, 36 ins. dia., bears N.22°W., 67 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Fir, 30 ins. dia., bears S.67°E., 34 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 67.00 Branch, 2 lks. wide, flows N.; ascend.
- 72.00 Top of hill; descend.
- 98.50 The cor. to secs. 17, 18, 19 & 20.

May 15th, 1884.

North between secs. 17 & 18.

V.20 $\frac{1}{2}$ °E.

Descend.

- 13.50 Smith River, 200 lks. wide, flows NW.; cross bottom.
- 40.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which
- Fir, 40 ins. dia., bears N.87°E., 58 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Fir, 40 ins. dia., bears S.62°W., 9 lks. dist.,
marked $\frac{1}{4}$ S B T.
- John Dally's cabin N.60°W., 4 chs. dist.
- 46.50 Cross south branch Twin Sisters, 50 lks. wide, flows W.
- 50.00 Ascend.
- 52.00 Descend.
- 58.00 North branch Twin Sisters, 40 lks. wide, flows W.
- 80.00 Set post, 6 ins. dia., 4 ft. long, in ground 12 ins. with
marked stone, for cor. to secs. 7, 8, 17 & 18, marked