

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 8 W.

CHAINS

V. 20 $\frac{1}{2}$ °E.

- 40.00 Set temp. qr. sec. cor.
- 98.50 Intersect West boundary, 50 lks. North of cor. to secs. 12, 13, 7 & 18; thence N. 89° 41' East, on true line, bet. secs. 7 & 18. On mountain top.
- 58.50 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- Hemlock, 10 ins. dia., bears N. 54° E., 8 lks. dist., marked $\frac{1}{4}$ S B T.
- Hemlock, 10 ins. dia., bears S. 40° W., 15 lks. dist., marked $\frac{1}{4}$ S B T.
- 62.00 Descend.
- 72.00 Branch, 10 lks. wide, flows S.; ascend.
- 98.50 The cor. to secs. 7, 8, 17 & 18.

North between secs. 7 & 8.

V. 20 $\frac{1}{2}$ °E.

Along East slope.

- 22.00 Cross ridge, along west slope.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Cedar, 36 ins. dia., bears S. 60° W., 42 lks. dist., marked $\frac{1}{4}$ S B T.
- Cedar, 24 ins. dia., bears N. 55° E., 29 lks. dist., marked $\frac{1}{4}$ S B T.
- 63.00 Cross spur; descend.
- 75.00 Branch, 1 lk. wide, flows W.; ascend.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 5, 6, 7 & 8, marked T 20 S S 5 on NE., R 8 W S 8 on SE., S 7 on SW., S 6 on NW. face, with 5 notches on S. & E. edges; from which