

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 19 S., R. 8 W.

CHAINS

and 1 notch on S. edge; from which

A fir, 10 ins. dia., bears N. $46\frac{3}{4}^{\circ}$ W., 79 lks. dist.,
marked T 19 S R 8 W S 25 B T.

A fir, 10 ins. dia., bears S. $61\frac{1}{2}^{\circ}$ W., 87 lks. dist.,
marked T 19 S R 8 W S 36 B T.

July 30th, '91.

North on E. bdy. of Sec. 25.

Va. observed at 8 a.m. $20^{\circ}30'E$.

Continue along W. side of same ridge, near top.

13.75 Cross top of same, c NW. & SE.; descend.

20.00 Into hollow, c E., 180 ft. deep.

26.50 Cross same ridge, c NE. & SW.; descend.

40.00 In a hollow, c NW., 300 ft. deep.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,
for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ S on W. face; from which

A maple, 10 ins. dia., bears S. $54\frac{1}{2}^{\circ}$ W., 9 lks. dist.,
marked $\frac{1}{2}$ S B T.

A fir, 10 ins. dia., bears S. $33\frac{1}{2}^{\circ}$ E., 48 lks. dist.,
marked $\frac{1}{2}$ S B T.

49.90 Fir, 12 ins. dia.

55.00 Top of same ridge, c NE. from SE.

72.25 Fir, 48 ins. dia.

79.31 Fir, 48 ins. dia.

80.00 On W. side of ridge, about 600 ft. lower than S. end of
mile.

Set post, $4\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground,
for cor. to secs. 24 & 25, marked T 19 S R 8 W S 24 on
NW., T 19 S R 8 W S 25, on SW. faces, with 2 notches on
S. and 4 notches on N. edges; from which

A dogwood, 6 ins. dia., bears S. 15° W., 26 lks. dist.,
marked T 19 S R 8 W S 25 B T.

A laurel, 10 ins. dia., bears N. $31\frac{1}{2}^{\circ}$ W., 50 lks. dist.,
marked T 19 S R 8 W S 24 B T.